



1.2) If A is spatially immobilized and B is free in the medium, the reaction causes a net transient gradient (current density) of B toward A. This transient current creates a temporary potential difference in the medium.

and/or Motion in a Sample Inventor: Pourmand, Nader Application No.: 10/040,030 Atty. Docket No. STAN-241




and/or Motion in a Sample Inventor: Pourmand, Nader Application No.: 10/040,030 Atty. Docket No. STAN-241



1.4.b) C and D are added asymmetric to the electrodes and an ionic perturbation is generated.

and/or Motion in a Sample Inventor: Pourmand, Nader Application No.: 10/040,030 Atty. Docket No. STAN-241




and/or Motion in a Sample Inventor: Pourmand, Nader Application No: 10/040,030 Atty. Docket No. STAN-241


5/35

2.1 Planar sensor design example:

Electrodes are inert and do not interact with the medium.
 The target molecules are immobilized on the (+) electrode.
 The (-) electrode is the reference electrode.
 A differential amplifier subtracts the voltage from the two electrodes.



## **2.2** Example of signal generated when no binding at the surface occurs: 1) Electrodes are inert and do not interact with the medium. 2) The target molecules are immobilized on the (+) electrode. 3) The (-) electrode is the reference electrode. 4) A differential amplifier subtracts the voltage of the two electrodes.




a) Solution is delivered symmetric to the electrodes With 0.1 pmol immobilized ssDNA,

b) Solution is delivered asymmetric to the electrodes With 0.1 pmol immobilized ssDNA.

10140343 64348

## 2.3 Example of signal generated when binding at the surface occurs:


- Electrodes are inert and do not interact with the medium.
   The target molecules are immobilized on the (+) electrode.
   The (-) electrode is the reference electrode.
   A differential amplifier subtracts the voltage from the two electrodes.



a) Solution is delivered symmetric to the electrodes, Polymerization of 0.1 pmol primed ssDNA.

b) Solution is delivered asymmetric to the electrodes Polymerization of 0.1 pmol primed ssDNA.

8/35




a) Movement and diffusion of molecules.

Addition of specific Nucleotide one at a time or all at the same time Addition of Enzyme Enzyme Right nucleotide added and signal generation Hybridization of DNA/RNA to primer DNA/RNA fragment Active electrode Gene specific primer ပ္ပ

FIGURE 3: Sequencing

Addition of specific nucleotide Addition of Enzyme Enzyme Hybridization of RNA to Specific primer Correct nucleotide generates signal RNA fragment SNP Active electrode FIGURE 4:1 SNP detection by using Total RNA Gene specific designed primer around the SNP


11/35



SNP detection by using

FIGURE 4:3

12/35



Perfect match primer/template polymerizes and signal is generated

FIGURE 5: SNP detection by using PCR product Title: Transient Electrical Signal Based Methods and Devices for Characterizing Molecular Interaction and/or Motion in a Sample Inventor: Pourmand, Nader Application No.: 10/040,030 Atty. Docket No. STAN-241


Addition of specific nucleotide Right nucleotide added and signal generation SNP Enzyme Addition of Enzyme PCR fragment Primer Active electrode Annealing the specific designed primer around the SNP

SNP detection by using Exonuclease/


FIGURE 6:

Degrading enzyme

14/35



15/35



Addition of enzyme and dNTP Only the hybridized primer will polymerize and generates signal Denaturing and hybridization of pathogens DNA/RNA Pathogens DNA Yout Immobilization of Pathogen specific primer

FIGURE 8: Pathogen typing

17/35




FIGURE 9: Antigen-antibody detection

18/35





FIGURE 10: Protein-protein interaction



Ligand and receptor detection FIGURE 11:

20/35







FIGURE 12: Hybridization






22/35






24/35



25/35








Figure 17 B: Basic model of the sensor with a differential amplifier





Figure 18 A: some sample charge sequencing extension signatures for 300 bp DNA

and Devices for Characterizing Molecular Interaction and/or Motion in a Sample Inventor. Pourmand, Nader Application No.: 10/040,030 Atty. Docket No. STAN-241







Figure 18 B: More sample charge sequencing extension signatures for 300 bp DNA with two different concentration of Immobilized DNA (0.05 pmol and 0.1 pmol)

29/35







FIGURE 18E


and/or Motion in a Sample Inventor: Pourmand, Nader Application No.: 10/040,030 Atty. Docket No. STAN-241

31/35



Title: Transient Electrical Signal Based Methods and Devices for Characterizing Molecular Interaction and/or Motion in a Sample Inventor: Pourmand, Nader

Inventor: Pourmand, Nader Application No.: 10/040,030 Atty. Docket No. STAN-241 32/35



33/35




Figure 20

34/35




Figure 21

35/35

Figure 22

